

### **Technical** Data Sheet



#### **Typical Inspection Data:**

Density @ 20°C	1.074 g/cm3
Appearance	Clear green/blue liquid

## **Super Coldmaster**

Ready to Use

# Recommended by Comma for applications requiring:

 Based on concentrate that conforms to: BS6580:2010; AFNOR NFR 15-601

#### **Product Features:**

- A Mono Ethylene Glycol (MEG) based engine coolant.
- Suitable for use in all types of vehicle requiring an MEG coolant.
- Suitable for Ferrous and Aluminium engines.
- -36 Winter protection.
- +45 Summer protection.
- 2 years full protection.
- Helps prevent winter freezing and summer boil over. Also improves heat transfer.
- NAP (Nitrite, Phosphate and Amine) free.

#### **Directions for use:**

- Ready to use, but for maximum protection first drain and flush cooling system.
- For full protection do not mix with other fluids.
- Minor spills should be soaked up with oil absorbent granules, sand or dirt. The spillage site should then be washed with soapy water and dried.

#### Handling:

- Remove spills from paintwork immediately.
- Keep away from foodstuffs and oxidising agents.
- Store in airtight container.
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product.

#### **Shelf Life:**

- 3 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

20-11-2014